

Electrolux Modular Static Preparation

Hot cupboards with sliding doors

The Electrolux Modular preparation range allows Professional caterers to design the preparation area of their kitchens providing heavy-duty specifications and features, high hygiene standards and extremely flexible modular functions. The modular design of the range is in line with our high benefit guidelines making it possible to combine worktops and sink tops with ambient, hot, refrigerated and freezer units (with solid hinged doors or special smooth telescopic drawers), offering big storage space thanks to its various lengths. The units are 700 mm deep with a work height of 900mm (710mm big storage inner space, 40mm sturdy worktops and 150mm adjustable oversized feet with optional clipping plinth). The models detailed on this sheet are 3 hot cupboards with sliding doors.



MATERIALS

- Hot cupboards with sliding doors are completely made of 304 AISI stainless steel with Scotch-Brite finishing.
- Hot cupboards units are supplied with a channeled ventilation system (2 way outputs) that allows a correct airflow and even temperature inside the storage area.
- Fan assisted heating via amored elements assures temperature range from 30° to 90°C.
- Detachable control panel with mechanical thermostat and on/off green indicator light and orange indicator light for heating element operation.
- Front and rear longitudinal stainless steel c-channel reinforcement 15/10 thickness.

- The internal sides, which support the structure, have a 3 level position 30 mm high middle-shelf in AISI 304 stainless steel with a central S/S support to avoid twisting.
- Sound deadening reinforcements between internal and external side panels strengthen the structure.
- Sliding doors incorporate sound deadening internal panels.

INSTALLATION

- Units are mounted on 150 mm height adjustable (0/+90 mm) oversized (65x65 mm) feet.
- Masonry installation feasible by simply removing feet.

CLEANING






- Extremely easy to clean thanks to the smooth edges avoiding any safety problem with daily use.
- 45° degrees internal side corners junction system and internal middle-shelf, height-adjustable in 3 positions, with an inner double fold to eliminate gaps between sides and back.
- All models comply with the strict international standards regarding hygiene and cleanability.



CE  **Electrolux**


121906

121908



I = CONNESSIONE ELETTRICA
ELECTRICAL CONNECTION




CODE NUMBER	EDITION	DATE
TE2SE12	01	05.08.11
Serial n°: 121906 - 121908 - 121902		



I = CONNESSIONE ELETTRICA
ELECTRICAL CONNECTION

CODE NUMBER	EDITION	DATE
TE2SE16	01	05.08.11
Serial n°: 121906 - 121908 - 121902		

121922



I = CONNESSIONE ELETTRICA
ELECTRICAL CONNECTION

CODE NUMBER	EDITION	DATE
TE2SE12	01	05.08.11
Serial n°: 121906 - 121908 - 121902		

Electrolux Modular Static Preparation

Hot cupboards with sliding doors

ADDD010

2013-10-03

	TE2SE12 121906	TE2SE16 121908	TE2SE20 121922
PAIGALDUSJONIS			
EI - Elektrühendus	230 V, 1, 50/60	230 V, 1, 50/60	230 V, 1, 50/60
TEHNILISED ANDMED			
Välismõõtmed -mm/laius	1200	1600	2000
Välismõõtmed -mm/sügavus	680	680	680
Välismõõtmed -mm/kõrgus	860	860	860
Ukse tüüp	Libisev	Libisev	Libisev
Uste arv	2	2	2
Võimsus - kW			
paigaldatuna-elekter	1.6	1.8	2
Netokaal - kg	83	102	121
Pinge	230 V, 1, 50/60	230 V, 1, 50/60	230 V, 1, 50/60

Võib muutuda ilma etteatamata