

Electrolux Modular Static Preparation

Ambient units with sliding doors

The Electrolux Modular preparation range allows Professional caterers to design the preparation area of their kitchens providing heavy-duty specifications and features, high hygiene standards and extremely flexible modular functions. The modular design of the range is in line with our high benefit guidelines making it possible to combine worktops and sink tops with ambient, hot, refrigerated and freezer units (with solid hinged doors or special smooth telescopic drawers), offering big storage space thanks to its various lengths. The units are 700 mm deep with a work height of 900mm (710mm big storage inner space, 40mm sturdy worktops and 150mm adjustable oversized feet with optional clipping plinth). The models detailed on this sheet are 3 ambient units with sliding doors and a length varying from 1200 to 2000 mm.



121816 + 855824

MATERIALS

- Ambient units are completely made of 304 AISI CrNi 18/10 stainless steel with Scotch-Brite finishing.
- Front and rear longitudinal stainless steel c-channel basement reinforcement 15/10 thickness (16 gauges).
- The internal sides, which support the structure, have a 3 level position 30 mm high middle-shelf in AISI 304 stainless steel with a central S/S support to avoid twisting.

- Sound deadening reinforcements between internal and external side panels strengthen the structure.
- Sliding doors incorporate sound deadening internal panels.

INSTALLATION

- Ambient units are mounted on 150 mm height adjustable (0/+90 mm) oversized (65x65 mm) feet.
- Masonry installation feasible by simply removing feet.

CLEANING

- Extremely easy to clean thanks to the smooth edges avoiding any safety problem with daily use.
- 45° degrees internal side corners junction system and internal middle-shelf, height-adjustable in 3 positions, with an inner double fold to eliminate gaps between sides and back.
- Hinges are incorporated on the inner sides for better hygiene.
- All models comply with the strict international standards regarding hygiene and cleanability.



Electrolux

	TE2S12 121924	TE2S16 121926	TE2S20 121928
TEHNILISED ANDMED			
Välismõõtmed -mm/laius	1200	1600	2000
Välismõõtmed -mm/sügavus	680	680	680
Välismõõtmed -mm/kõrgus	860	860	860
Välismõõtmed -mm/kõrguse reguleerimine	50	50	50
Kapp			
laius - mm	1030	1430	1830
sügavus - mm	620	620	620
kõrgus - mm	645	645	645
Ukse tüüp	Libisev	Libisev	Libisev
Uste arv	2	2	2
Netokaal - kg	79	97	115