

# Salamanders Electric Salamander, open on 3 sides - 600mm

ITEM #		
MODEL #		
NAME #		
SIS #		
AIA #		



283014 (E0UUAEBOMOA)

Electric Salamander, open on 3 sides, 600 mm, accepts

283015 (E0UUADBOMOA)

Electric Salamander, open on 3 sides, 600 mm, accepts GN 1/1

# **Short Form Specification**

#### Item No.

Constructed in AISI 304 stainless steel. Table top model can be hanged on the wall with wall brackets (optional). Open on 3 sides. Incoloy heating elements placed in the upper deck, and can be tilted for easy cleaning. Upper desk is movable, sliding up and down along runners. 2 independent cooking areas managed by 2 separate energy regulator. Air vents along the upper side for evacuating heat and smoke. Extractable drip trays and chromium-plated steel grids for easy cleaning.

#### **Main Features**

- 2 indipendent tilting incoloy armoured heating elements.
- Cooking plate size: 600 x 350 mm accept GN 1/1.
- Heat control with energy regulator.
- Open 3 sides for rapid cooling and ease of use.
- Heating elements can be tilted for easy cleaning under the moving deck.

#### Construction

- Made of AISI 304 stainless steel.
- Air vents along the upper side for evacuating heat and smoke.
- Removable stainless steel drip tray.
- Movable upper plate.
- Chromium-plated steel grid with a safety stop to avoid accidental fall.
- Table top unit can be wall mounted with dedicated optional accessory.
- 4 rubber feet.

## **Optional Accessories**


•	Wall mounted brackets kit for	PNC 283035
	salamanders open on 3 sides	

APPROVAL:





# **Salamanders** Electric Salamander, open on 3 sides - 600mm



ONVGL CE IEC IECE

## Electric

Supply voltage:

283014 (E0UUAEBOMOA) 230 V/1 ph/50/60 Hz 283015 (E0UUADBOMOA) 380/415 V/3N ph/50/60 Hz 4 kW

Electrical power max.:

## **Key Information:**

External dimensions, Width: 600 mm External dimensions, Height: 510 mm External dimensions, Depth: 549 mm Net weight: 48 kg

Salamanders Electric Salamander, open on 3 sides - 600mm